

PRODUCT DESCRIPTION

Procura Ignite is a high-performance backlit textile designed for direct or transfer sublimation. Its soft, uncoated white face handles high-ink loads without bleeding, while the coated side is compatible with UV inks. It’s crease-resistant and recovers well under tension, ensuring top-notch performance for your projects.

SPECIFICATION

CHARACTERISTICS	METRIC	IMPERIAL
FABRIC CONTENT	100% Polyester, PVC Free	
WEIGHT	170 g/m2 (±3 %)	5.0oz (±3 %)
HEAT SET TEMPERATURE	180 - 230 °C	356 - 446°F
CALIPERED THICKNESS	0.25 mm	0.01 in

APPLICATIONS

	Geometric Displays	SEG Graphics	Exhibit Graphics	Backdrops	Procura Décor	Acoustic Walls	Lightboxes
Applications		■	■	■	■		■

PRINT TECHNIQUES

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
		■	■		■	■

AVAILABLE WIDTHS

Metric (cm)	Imperial (inches)
160, 252, 320, 505	63, 99, 126, 198



FR Ratings

B-s1, d0 DIN EN 13501-1

NFPA 701

FEATURES

- Bruise Free
- Crease resistant
- Air Tight
- Slight Elasticity
- Foldable
- Flame Retardant
- 70% Translucency

CERTIFICATIONS



DISCLAIMER

The provided information regarding physical and chemical characteristics is derived from tests we consider reliable. These values are intended solely for informational purposes. Please note that no legally binding guarantee of specific properties should be inferred from our specifications. They are presented without any form of assurance and do not establish a warranty. Prior to usage, it is the responsibility of the purchaser to independently assess the suitability of this material for their particular purpose. Please keep in mind that the data represents averages and is not meant for use as an official specification.