

PRODUCT DESCRIPTION

A lightweight 3oz. fabric woven from 100% knitted polyester, resists bleed-through for vivid designs. It complies with REACH regulations, and it’s versatile, supporting multiple printing methods.

SPECIFICATION

CHARACTERISTICS	METRIC	IMPERIAL
FABRIC CONTENT	100% Polyester	
WEIGHT	100 g/m2 (±3 %)	3.0oz (±3 %)
HEAT SET TEMPERATURE	180 - 230 °C	356 - 446°F
CALIPERED THICKNESS	0.25 mm	0.01 in

APPLICATIONS

	Geometric Displays	SEG Graphics	Exhibit Graphics	Backdrops	Procura Décor	Acoustic Walls	Lightboxes
Applications		■	■	■	■	■	

PRINT TECHNIQUES

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
		■	■		■	■

AVAILABLE WIDTHS

Metric (cm)	Imperial (inches)
320, 505	126, 198



FR Ratings

B-s1, d0

NFPA 701

DIN EN 13501-1

M1 – NF P 92 503-507

FEATURES

- Crease resistant
- Excellent Bleed Through
- Foldable
- Flame Retardant

CERTIFICATIONS



DISCLAIMER

The provided information regarding physical and chemical characteristics is derived from tests we consider reliable. These values are intended solely for informational purposes. Please note that no legally binding guarantee of specific properties should be inferred from our specifications. They are presented without any form of assurance and do not establish a warranty. Prior to usage, it is the responsibility of the purchaser to independently assess the suitability of this material for their particular purpose. Please keep in mind that the data represents averages and is not meant for use as an official specification.